

## HDC-SD210BAS HDC-SD210BASM Comparison Table



| Section  | HDC-SD210BAS   | HDC-SD210BASM                   |
|--|--|---------------------------------|
| Video Out (PE10055 Video Signal / Output Resolution) | 1920 x 1080 30p / 1920 x 1080 30p<br>1920 x 1080 30p / 1920 x 1080 60i |                                 |
| Output Format / Interface: SDI                       | HD-SDI, SMPTE-292M / 75 Ω BNC  |                                 |
| Composite  | 1V p-p, NTSC, PAL / 75 Ω BNC   |                                 |
| S-Video  |  | Y-C, NTSC, PAL / Mini-DIN       |
| HDMI   |  | HDMI 1.3 / HDMI c-type          |
| Analog Component                                     |  | 700mV p-p Y-Pb-Pr / 75 Ohm 3RCA |
| Gen-Lock   |  | Yes                             |
| Operation Temperature                                | 32°F ~113°F (0°C~45°C)   |                                 |
| Operation Humidity                                   | 20 to 80%  |                                 |
| Camera Module Control                                | Remote Control / RS-232  |                                 |
| OSD  | Yes (16 Colours) / OSD Menu / OSD Caption                              |                                 |
| Power  | DC 12V (Voltage Tolerance: 8V~15V)                                     |                                 |
| Power Consumption: Camera                            | DC 12V / Max. 500mA  | DC 12V / Max. 720mA             |
| Weight   | 440± 10g   | 485± 10g                        |
| Dimension  | 67.5(W) x 166.9(L) x 65.7(H)   |                                 |

Kane Computing Ltd,  
 7 Theatre Court, London Road, Northwich, Cheshire, CW9 5HB.  
 Tel: +44(0)1606 351006 - Fax: +44(0)1606 351007/8  
 Email: sales@kanecomputing.com - Web: www.kanecomputing.co.uk